



## Model S30 Specifications

## **INDUSTRIAL POWER SWEEPER**

Feature			
Sweeping System			
Cleaning path			
Single side brush		62.5-inch	1,590 mm
Dual side brush		80-inch	2,030 mm
Main brush			
Main brush length (tubular)		45-inch	1,145 mm
Main brush lift		Mechanical or Hydraulic	Mechanical or Hydraulic
Main brush change		No-tool	No-tool
Side broom			
Side broom diameter		26-inch	660 mm
Debris hopper			
Volume capacity (plastic)		14 ft <sup>3</sup>	395 liter
Weight capacity (plastic)		1,080 lb	490 kg
Volume capacity (steel)		14 ft <sup>3</sup>	395 liter
Weight capacity (steel)		1,200 lb	545 kg
Dump height (variable to)		60-inch	1,525 mm
<b>Dust Control System</b>			
Filter system (triple stage)			
Stage 1		Perma-Filter™	Perma-Filter™
Stage 2		Cyclonic Pre-filter	Cyclonic Pre-filter
Stage 3		80.8 ft <sup>2</sup> cylindrical filter	7.5 m <sup>2</sup> cylindrical filter
Dust filtration (to) @99% efficiency		.5 microns	.5 microns
Vacuum fan speed			
Normal sweeping mode		4,600 rpm	4,600 rpm
Litter sweeping mode		5,500 rpm	5,500 rpm
Vacuum diameter		11-inch	280 mm
Propelling System			
Propel speed forward (variable to)		8.0/13.0 mph	13.0/21.0 km/h
Propel speed reverse (variable to)		3.0 mph	5.0 km/h
Engine-gasoline/LPG		55 hp GM	41 kW GM
Engine-diesel		37.5 hp Kubota	28 kW Kubota
Gradeability		·	
Full hopper		10 deg/18%	10 deg/18%
Empty hopper		14 deg/25%	14 deg/25%
<b>Machine Dimensions</b>			
Length		93-inch	2,360 mm
Width		62.5-inch	1,590 mm
Height			,
With overhead guard		82.5-inch	2.095mm
		58-inch	1,475 mm
Without overhead guard			
Without overhead guard Weight (net)		3,520 ID	1,595 KQ
Without overhead guard Weight (net) Minimum aisle turn		3,520 lb 113-inch	1,595 kg 2,870 mm