ATLV[®] 4300



All-terrain Litter Vacuum

- Improves the image and health of your community with superior litter pickup
- Increases productivity by adapting to all terrains
- Ensures operator safety with stable, low-center-of-gravity design

The safe and efficient solution for all-terrain, outdoor sweeping

Tennant built the 4300 ATLV to tackle real-world operating conditions. Whether climbing over curbs, navigating hills or cleaning along fence lines, the rugged ATLV 4300 delivers. The ATLV keeps all your outdoor surfaces clean. From asphalt and concrete to turf and grass, you'll always make a good first impression.

Improve the image and health of your community


The high-performance vacuuming power of the ATLV, complemented by its long-arm vacuum, all-terrain tires and curb-climbing ability, keep grassy grounds, parking lots, fence lines and shrub beds free of trash, cigarette butts, bottles and more.

Maximize productivity

Easy-to-use features require less training time, so operators get out and cleaning more quickly. During operation, a quick peak through canister portholes reveals the debris level in the ATLV's unmatched, extra-large-capacity hopper. Operators effectively clean longer between stops, knowing that the top-mounted vacuum fan continually provides unrestricted airflow. Empties go smoothly with the wide-angle, tilt-out litter tank for easy-access debris removal.

Rely on safe, stable operation

Clean with confidence knowing that the ATLV provides safe, stable operation with its low center of gravity design, highly effective disk brakes and standard rollover protection system.



MUST-HAVE OPTIONS

Extend your cleaning reach

Access the vacuum hose for additional cleaning reach with the optional fenceline nozzle.

Control dust

Water assisted dust control configurations help contain air-borne dust.

Make cleaning comfortable

Add a ROPS certified cabin for comfort from the elements.



LONG-LASTING AND DURABLE

A corrosion-resistant polyethylene canister with optional bagless liners, as well as the self-cleaning impeller inlet screen, keeps the ATLV cleaning and looking better longer.





A	Four all-terrain tires maximize mobility and minimize ground compaction.	ROPS certified overhead bar provides operator protection from rollovers.
B	Easy cleanout, quick access, swing out hydraulic cooler.	Ergonomic design includes power/tilt steering and the easy-access vacuum hose.
C	Debris container uses standard, off-the-shelf trash bags for lower supply costs. Container tilts out for easy cleaning.	Adjustable vacuum hose can be repositioned for easy litter pick-up.
D	Top-mounted vacuum fan design ensures debris will not go though the vacuum fan.	High ground clearance accommodates uneven terrain and street curbs.



WARRANTY — All parts (excluding batteries) have a 24-month / 2,000 hours of operation warranty under normal use and service. On-site labor coverage of warranty items for six (6) months.

GENUINE TENNANT PARTS, SUPPLIES & SERVICE

Genuine Tennant Parts Advantage

Operate your machine with confidence by choosing genuine Tennant parts. Only authentic Tennant parts are engineered in conjunction with Tennant equipment. For years of worry-free operation, accept only genuine parts and supplies.

Industry's Only Factory-Direct Service Network

Tennant offers the only factory-trained, locally based network of 400+ service techs dedicated to keeping your cleaning program up and running.

CONVENIENT & FLEXIBLE PURCHASING OPTIONS

Trust the industry leader to best understand your financing needs. Tennant Financial Services understand how you use your equipment, its value over time and how marketplace changes may affect you.

SEEING IS BELIEVING

See for yourself how the ATLV litter vacuum can improve your community image. For a demonstration and additional information, call 800.553.8033.

4300 ALL TERRAIN LITTER VACUUM

FEATURES

Туре	Vacuum nozzle	Vacuum nozzle
Time required to cover a football field	1/2-hour	1/2-hour
Debris hopper		
Volume capacity	110 gal	416 L
Bag capacity-each	55 gal	208 L
Bag size	44 X 55 in, 3 mm	1120 X 1400 mm
Vacuum System		
Nozzle size (diameter)	8 in	200 rpm
Vacuum fan (diameter)	17 in	430 mm
Propelling System		
Propel speed forward (variable to)	16.0 mph	26.0 km/h
Propel speed reverse (variable to)	5.0 mph	8.0 km/h
Propel motor		
Diesel, liquid cooled Kubota @3000rpm	28 hp	21 kW
Optional: Diesel, liquid cooled Kubota @3000r	pm 38 hp	28 kW
Туре	Hydrostatic	Hydrostatic
Motors	Both rear wheels	Both rear wheels
Hydraulic		
Pumps	1 propelling,	1 propelling,
	1 accessory	1 accessory
Oil cooler	Fin type	Fin type
Gradeability		
Full & empty hopper	12.0 deg/21%	12.0 deg/21%
Machine Dimensions		
Length	102 in	2590 mm
Width	46 in	1170 mm
Height	84in	2130 mm
Weight-net base machine	1860 lb	844 kg
Turning radius	18 in	460 mm
5		

Tennant

P.O. Box 1452 Minneapolis, MN 55440-1452

800.553.8033 | 763.540.1200 In Quebec: 800.361.9050

www.tennantco.com info@tennantco.com